



Clouds 503 Cumulo



Clouds 508 Strato



Clouds 509 Nimbo



Clouds 512 Cirro



SPECIFICATIONS

Style Name	:	Clouds
Construction	:	Structured Loop
Fiber	:	100% PET (Polyester)
Yarn	:	BCF
Denier	:	2100 DN
Gauge	:	1/10 th Infinity
Pile Weight	:	500 gsm per sqm (+/-5%)
Total Weight	:	3500 gsm per sqm (+/-5%)
Stitches per 10 CM	:	45.5 (+/- 5%)
Tufted Pile Height	:	3 - 3.5 MM
Total Thickness	:	5.5 MM (+/-5%)
Primary Backing	:	Woven Poly Propylene
Secondary Backing	:	Extruded PVC Backing
Size	:	50 x 50 CM
Packing	:	20 PCS (5M ²) Per Box
Installation Method	:	Quarter Turn & Bricks

PERFORMANCE PARAMETERS

Flammability	:	ASTM D2859 - PASSES Federal Flammability Standard CPSC FF 1-70.
Smoke Density	:	ASTM E662 - PASSES the requirements of 450 or less.
Color Fastness to Water	:	AATCC 170 – Rating 5 (No Change)
Critical Radiant Flux	:	ASTM E648 - Meets or exceeds Class 1 rating as per NFPA Life Safety Code 101.
Hexapod Tumble Drum Tester	:	ASTM D5252 – No Visual Change Noticeable in Appearance

- All pictures shown are for illustration purpose only. Actual product may vary due to product enhancement.